

JET

We are a full-line Jet distributor, stocking many machines and equipment. Jet has frequent promotions and sales on their equipment, so in order to stay up to date on prices and inventory please call Ballew Saw & Tool, Inc. **1-800-288-7483**.

**16-32 Plus Drum Sander****Standard Equipment:**

- One Abrasive Strip, 80 Grit
- One 100 Grit Abrasive conveyor belt
- TufTool™ for wrapping abrasives on sanding drums
- Metal stand with shelf
- One box of Ready to Wrap™ abrasives

Sanding Capacity:

- Max Width: 32" (Two Passes)
- Max Length: 2-1/4"
- Max Thickness: 3"
- Min. Thickness: 1/32"

Motor (TEFC):

- 1-1/2HP, 1Ph, 110V

629004K

Specifications:

- Dimensions (H x W x D): 18" x 23" x 32"
- Drum Dimensions (Dia. x L): 5" x 16"
- Drum Speed: 1725 RPM
- Drum Bearing Diameter: 1"
- Dust Port Diameter: 4"
- Conveyor Motor: 43 in.-lbs. Torque, Direct Drive D.C.
- Conveyor Variable Feed Rate: 0 to 10 Feet Per Minute
- Net Weight: 164 lbs.

Optional Accessories for Model 16-32

PART#	DESCRIPTION
61-1012	Poly Conveyor Belt
98-0130	Set of 4 Casters
98-1601	Infeed and Outfeed Tables

22-44 Plus Drum Sander

Standard Equipment:

- One Abrasive Strip, 80 Grit
- One 100 Grit Abrasive conveyor belt
- TufTool™ for wrapping abrasives on sanding drums

Motor (TEFC):

- 1-3/4HP, 1Ph, 115V, 20 amp

Specifications:

- Drum Dimensions (Dia. x L): 5" x 22"
- Drum Speed: 1700 RPM
- Dust Port Diameter: 4"
- Conveyor Motor: 43 in.-. Torque, Direct Drive D.C.
- Conveyor Variable Feed Rate: 0 to 10 Feet Per Minute
- Net Weight: 649003K - 254 lbs., 649004K - 296 lbs., 649005K - 345 lbs.

Sanding Capacity:

- Max Width: 44" (Two Passes)
- Max Length: 2-1/4"
- Max Thickness: 4"
- Min. Thickness: 1/32"

- 649003K (Bench top Style)
- 649004K (Open Stand Style)
- 649005K (Closed Stand Style)



Optional Accessories for Model 22-44

PART#	DESCRIPTION
609004	Open Stand with Shelf
98-0130	Set of 4 Casters for Open Stand Style Only
609005	Closed Stand with Shelf and Casters
98-2202	Infeed and Outfeed Tables

10-20 Plus Drum Sander



Standard Equipment:

- One Abrasive Strip, 80 Grit
- One 100 Grit Abrasive conveyor belt
- TufTool™ for wrapping abrasives on sanding drums

Motor (TEFC):

- 1HP, 1Ph, 115V

Specifications:

- Drum Dimensions (Dia. x L): 5" x 10"
- Drum Speed: 1700 RPM
- Dust Port Diameter: 4"
- Conveyor Motor: 43 in.-lbs. Torque, Direct Drive D.C.
- Conveyor Variable Feed Rate: 0 to 12 Feet Per Minute
- Net Weight: 74 lbs.

Sanding Capacity:

- Max Width: 20" (Two Passes)
- Max Length: 2-1/4"
- Max Thickness: 3"
- Min. Thickness: 1/32"

628900

Optional Accessories for Model 10-20

PART#	DESCRIPTION
638004	Open Stand with Shelf
98-0130	Set of 4 Casters for Open Stand Style Only