



**PANASONIC****EY6432GQKW (15.6V / 3.5Ah Ni-MH)  
Cordless 1/2" Drill & Drive Kit**

- High capacity 3.5Ah Ni-MH battery
- Compact body (Length 8-3/16")
- Light Weight (4.8 lbs.)
- High Power (390 in.lbs.)
- 55 min. charging system\*
- Variable speed control / reversible
- 18-stage clutch plus drill position
- 1/2" heavy-duty keyless chuck
- 2-speed gear box
- Electric brake
- New ergonomic design
- Extra battery pack as standard equipment



**Max. Torque** .....390 in.lbs.  
**Speed at No Load**....Low 65-450 rpm, High 200-1,450 rpm  
**Clutch Torque** .....9-61 in.lbs. (3.0 in.lbs. per stage, total 18 stage) (approx.) (max torque at drilling position-stage 19)  
**Charging Time** .....55 minutes (using EY0230B charger)\*  
**Weight** .....4.8 lbs.  
**Size (LxHxW)** .....8-3/16" x 9" x 2-9/32"  
**Spindel Thread** .....3/8"-24

Typical Applications: General construction, Plumbing, Finishing carpenter and Electrical installation work.

**EY7201GQKW (12.0V / 3.5Ah Ni-MH)  
Cordless Impact Wrench / Driver**

- High capacity 3.5Ah Ni-MH battery
- Hard and Soft Torque modes to accommodate both heavy and lightweight jobs
- Advanced ergonomic design with better grips to improve tool handling and the application of force
- Front mounted LED light to allow for easier work in dark places
- Move around hands free by hooking the tool directly to your belt.
- Rubber guards help prevent the tool and material surface from damage.



**Max. Torque** .....Hard Mode 0-2600 rpm, Soft Mode 0-2200 rpm  
**High Power** .....Hard Mode 1060 in.lbs., Soft Mode 711 in.lbs.  
**Chuck** .....1/4" Hex drive  
**Charging Time** .....55 minutes (using EY0110B charger)\*  
**Weight** .....3.9 lbs.  
**Size (LxHxW)** .....9.25" x 2.28" x 6.44"

Typical Applications: Air conditioning installation, Automotive repair and maintenance, Assemble and disassemble scaffolding and Long wood screw / lag screw fastening.

**EY6225CQ (3.6V)  
Cordless Drill & Driver Kit**

- "Auto Shut-off Clutch" extends battery and clutch life by immediately stopping rotation once selected torque setting is reached
- Powerful: 39 in.lbs. (at low speed)
- High speed: 600 rpm
- 22-stage clutch
- 1/4" hex quick connect chuck
- 15-minute charging system\*
- Easily converts from straight to pistol form
- EY6225C (without battery charger) is also available



**Max. Torque** .....Low 39 in.lbs., High 13 in.lbs.  
**Speed at No Load**....Low 200 rpm, High 600 rpm  
**Clutch Torque** / .....21 stages / 2.6-26 in.lbs.  
**Auto Shut-off Clutch**  
**Charging Time** .....15 minutes (using EY0225B charger)\*  
**Weight** .....1.15 lbs.  
**Size (LxHxW)** .....11-21/32" x 6-1/8" x 1-9/16"

Typical Applications: Rack / Cabinet installation, Electricians, Service engineers and Production line, assembly work.

\*Charging Times are approximate.

**EYC150GQKW (18V / 3.5Ah Ni-MH)  
Reciprocating Saw / Drill Driver Combo**

- High capacity 3.5Ah Ni-MH battery provides extended work periods
- The Reciprocating Saw is designed to handle the toughest demolition jobs
- Drill Driver built with new motor and gear systems which deliver more power and performance
- Both tools are designed with the latest ergonomic features to allow for maximum comfort and results
- Faster charging times giving you more time to work



**Max. Torque** .....442 in.lbs. for Saw and Drill  
**Speeds** .....Reciprocating Saw 0-2,700 rpm  
 Drill: Low 70-430 rpm, High 240-1500 rpm  
**Clutch** .....Drill: 15-stage plus drill position  
**Charging Time** .....65 minutes (using EY0110B charger)\*  
**Chuck** .....1/2"  
**Weight** .....Saw: 8.5 lbs / Drill: 57 lbs.

Typical Applications: General construction, Plumbing, Carpentry (Saw), Finishing carpentry (Drill) and Electrical installation work.

**EY3794B (12.0V) Cordless Flashlight**



**Voltage** .....12.0V  
**Bulb Type** .....Xenon 0.7A  
**Brightness** .....approx. 4,000 Lux  
**Adjustable Head Angle** .....Yes, 4 steps  
**Wide/Focus Adjustment** .....Yes  
**Low Battery Indication** .....Yes  
**Shoulder Strap** .....Yes  
**Acceptable Battery Packs** ....All Panasonic 12V  
**Dimensions (H x W x D)** .....11.02" x 3.75" x 3.75"  
**Weight** .....0.8 lbs

**EY3795B (15.6V) Cordless Flashlight**



**Voltage** .....15.6V  
**Bulb Type** .....Xenon 0.7A  
**Brightness** .....approx. 4,000 Lux  
**Adjustable Head Angle** .....Yes, 4 steps  
**Wide/Focus Adjustment** .....Yes  
**Low Battery Indication** .....Yes  
**Shoulder Strap** .....Yes  
**Acceptable Battery Packs** ....All Panasonic 15.6V  
**Dimensions (H x W x D)** .....11.02" x 3.75" x 4.33"  
**Weight** .....0.83 lbs

**EY3793B (15.6V) Cordless Lantern**



**Voltage** .....15.6V  
**Bulb Type** .....Xenon 7.2V, 0.75A  
**Brightness** .....approx. 5,000 Lux (up to 100 lumens)  
**Adjustable Head Angle** .....Yes, 4 steps  
**Shoulder Strap** .....Yes  
**Acceptable Battery Packs** ....All Panasonic 15.6V  
**Dimensions (L x H x W)\*** .....Max. 6-1/8" x 8" x 5-1/16"  
**Weight\*** .....0.93 lbs

\*Dimensions and Weight are without the battery

**Acceptable Battery Packs and Hours of Use**

- With 15.6V "type G" battery pack EY9231B: Approx. 7.2 hours
- With 15.6V "type N" battery pack EY9230B: Approx. 6 hours
- With 15.6V "type F" battery pack EY9136B: Approx 4 hours

**Other Panasonic Items Available**

EY6181CQKW	Drill and Driver
EY9230GQKW	Drill and Driver
EY6407NQKW	Drill and Driver
EY9061	Battery

*Pictures and descriptions not available for these products at this time.*

**EY9080B (9.6V) Compact Battery Pack**



**Battery Type** .....9.6V Ni-Cd 1.2Ah Type "D"  
**Charging Time** .....45 Minutes

**EY9086B (9.6V) Compact Battery Pack**



**Battery Type** .....9.6V Compact Short Stem Type "C"

**EY9200B (12.0V) Ni-MH Battery Pack**



**Battery Type** .....12V 3.0 Ah Ni-MH Capacity Type "N"  
**Charging Time** .....45 Minutes

**EY9106B (12.0V) Compact Battery Pack**



**Battery Type** .....12V 2.0 Ah Ni-Cd Ironman High Capacity Type "F"  
**Charging Time** .....30 Minutes

**EY9201B (12.0V) Ni-MH Battery Pack**



**Battery Type** .....12V 3.5Ah Ni-MH  
**Charging Time** .....55 Minutes with the EY0214B and EY0230B chargers

**EY9231B (15.6V) Ni-MH Battery Pack**



**Battery Type** .....15.6V 3.5Ah Ni-MH  
**Charging Time** .....55 Minutes with the EY0214B and EY0230B chargers